

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1367>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.000 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left/short edge: 1.26wx1.00h, 1.90 & 8.20 inches from bottom; cutout on bottom edge, 17.06wx1.16h, 2.80 from right edge; 2 cutouts on right edge, 1.262wx1.00, 2.40 from bottom and 1.26wx0.90h, at top corner; cutout on top, 4.28w, 4.50 from left edge, ending in circle with radius of 2.14, centered 8.34 from bottom; near side has crosswise grooves: 1.25wx1.30h along right edge and 2.48wx0.60h along left edge; a cutout 1.75w7.00hx0.75d, 4.50 from left edge and markings: part number near top right corner and "up" and "aft" on 2 lines below part number

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d