Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-1465

Fire Retarding Characteristic:

Not fire retarding

Width:

18.000 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.25wx1.00h, 2.20 & 14.60 inches from bottom; 3 cutouts on left edge: 1.00wx1.00h, 2.20 & 9.00 & 15.20 from bottom; 1 cutout on top edge, 4.28w, 6.08 from right edge, ending in circle with radius of 2.14 centered 9.00 inches from bottom; near side has markings: "up" and "aft" centered near top of left upper section and part number below it, near bottom groove (on far side); far side has 2 lengthwise grooves: 2.75wx0.70d along top edge and 2.40wx0.70d along bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d