

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1476>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.180 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left/short edge: 1.00wx1.00h, 2.26 & 15.20 inches from bottom; cutout 9.00wx7.00h from bottom right corner and arched cutout from bottom edge, 8.00wx11.00h, 3.00 in from left edge; a crosswise half-arched cutout from right edge, rounded side down, 9.00wx3.90h, 8.50 from bottom; and a cutout on right edge, 1.00wx1.00h, 2.58 from top; near side has a groove, 2.58wx0.84d along top edge, and has markings: "up" in top groove, and "aft" below it and part number to right of "aft"

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d