

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1476>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

18.180 inches

**Thickness:**

4.000 inches

**Length:**

22.320 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 2 cutouts on left/short edge: 1.00wx1.00h, 2.26 & 15.20 inches from bottom; cutout 9.00wx7.00h from bottom right corner and arched cutout from bottom edge, 8.00wx11.00h, 3.00 in from left edge; a crosswise half-arched cutout from right edge, rounded side down, 9.00wx3.90h, 8.50 from bottom; and a cutout on right edge, 1.00wx1.00h, 2.58 from top; near side has a groove, 2.58wx0.84d along top edge, and has markings: "up" in top groove, and "aft" below it and part number to right of "aft"

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T258-d