

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1530>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.760 inches

Thickness:

2.500 inches

Length:

21.070 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout on right/short lower corner: 5.00wx4.00h and cutout on top edge, 3.20wx10.06l, 10.68 inches from left edge; near side is tapered 0.30 at top edge; far side has crosswise groove 2.50wx0.60d along top edge and roughly rectangular-shaped surface cutout: 17.07wx11.00hx1.25d from bottom left corner and additional cutout along right edge, 4.00wx3.20hx1.25d, 7.20 inches from bottom edge and has markings "up" and "aft" on 2 lines below top groove on left side and part number on right side

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d