## NSN 9330-01-502-1530

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-1530

Fire Retarding Characteristic:
Not fire retarding
Width:
17.760 inches
Thickness:
2.500 inches
Length:
21.070 inches
End Application:
Aircraft, thunderbolt ii, a-10
Surface Condition:
Rough
Density Rating:
1.2 pounds per cubic foot
Compression Strength At 25 Pct Deflection:
0.35 pounds per square inch
Product Name:
Filler foam
Special Features:
Rectangular with cutout on right/short lower corner: 5.00wx4.00h and cutout on top edge, 3.20wx10.06l, 10.68 inches from left edge; near
side is tapered 0.30 at top edge; far side has crosswise groove 2.50wx0.60d along top edge and roughly rectangular-shaped surface cutout:
17.07wx11.00hx1.25d from bottom left corner and additional cutout along right edge, 4.00wx3.20hx1.25d, 7.20 inches from bottom edge
and has markings "up" and "aft" on 2 lines below top groove on left side and part number on right side
Material:
Plastic, polyurethane
Material:
Plastic polyurethane
Supplementary Features:
Material to be reticulated foam per sm-alc specification ms-mmrs-87-100
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T258-d