

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1583>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.660 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.26wx2.70h at bottom corner and 1.26wx3.66h at top corner; 3 cutouts on left edge: 1.00wx1.00h, 1.40 & 7.80 from bottom and 1.00wx1.40h, 13.40 from bottom; and a rectangular cutout from top edge: 6.50wx6.06h, 8.75 from left edge; near side has lengthwise grooves: 2.70wx2.25d along bottom edge and 2.36wx1.70d along top edge; a crosswise groove: 1.26w along right edge and has markings: "up" and "aft" on 2 lines near top left corner and part number under cutout

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d