

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1589>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.280 inches

Thickness:

4.000 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.25wx1.00h, 2.20 inches from bottom & 1.00wx4.00h at top corner; 3 cutouts on left edge: 1.00wx1.00h, 2.40 & 7.70 & 14.70 inches from bottom; a cutout on top edge: 3.40wx5.30h, 11.00 from left edge: near side has lengthwise grooves: 2.50wx1.80d along top edge and 2.40wx2.00d along bottom edge; and triangular cutout on right edge 1.25w starting on far side surface, 13.70 from bottom edge and slanting up to meet near side surface 8.40 from bottom edge; near side has markings: "up" & "aft" near upper right corner and part number centered above bottom groove; far side is tapered 0.40 at top edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d