

View Online at <https://aerobasegroup.com/nsn/9330-01-502-1700>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.090 inches

Thickness:

2.500 inches

Length:

22.320 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 2.00wx2.50h at bottom corner and 1.25wx1.12h, 12.25 from bottom; 3 cutouts on left: 1.00wx1.00hm 1.20 & 7.60 & 12.80 from bottom; and cutout on top edge: 6.50wx4.69h, 7.32 from left edge; near side has markings: "up" and "aft" near upper right corner and part number near left side about 5 inches from bottom; far side has 2 crosswise grooves: 1.25wx1.70d, 8.50 from right edge and 1.00wx1.70d, 7.32 from left edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d