Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-1981

Fire Retarding Characteristic:

Not fire retarding

Width:

16.360 inches

Thickness:

2.500 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 1 cutout on right/short edge: 1.16wx2.00h, 8.92 inches from bottom; 1 cutout on bottom edge: 16.73wx1.16h, 1.16 from right edge; 2 cutouts on left edge: 1.25wx1.00h, 2.96 & 13.80 inches from bottom edge; 1 cutout near center: 9.79wx2.00h, 8.92 from bottom and 7.30 from right edge with line cut through from right edge of cutout to right edge or item; near side is tapered 0.30 at bottom edge and has crosswise groove: 1.16wx1.16d along right edge and a cutout on left edge: 3.80wx2.00hx1.38d, 8.92 from bottom; far side has markings: "up" and "fwd" on 2 lines near center top and part number near center bottom

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d