

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2004>

Fire Retarding Characteristic:

Not fire retarding

Width:

14.600 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 1 cutout on right edge: 1.25wx5.50h, 3.85 inches from bottom; 2 cutouts on left edge: 1.25wx2.30h, 2.70 inches from bottom and 1.25wx3.00h, 9.48 from bottom; near side is tapered 0.56inch at bottom edge; far side has lengthwise groove: 2.50wx1.40h along top edge, a semicircular lengthwise groove with a radius of 2.00, 3.85 inches from bottom, and markings "up fwd" in top groove and part number near center bottom

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d