NSN 9330-01-502-2012

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-2012

13.600 inches Thickness: 2.000 inches Length: 14.000 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	
Width: 13.600 inches Thickness: 2.000 inches Length: 14.000 inches Length: 14.000 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Fire Retarding Characteristic:
Thickness: 2.000 inches Length: 14.000 inches End Application: Aircraft, thunderboth ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Not fire retarding
tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Width:
2.000 inches Length: 14.000 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	13.600 inches
Length: 14,000 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Thickness:
14.000 inches End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	2.000 inches
End Application: Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Length:
Aircraft, thunderbolt ii, a-10 Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	14.000 inches
Surface Condition: Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	End Application:
Rough Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Aircraft, thunderbolt ii, a-10
Density Rating: 1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Surface Condition:
1.2 pounds per cubic foot Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Rough
Compression Strength At 25 Pct Deflection: 0.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Density Rating:
O.35 pounds per square inch Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	1.2 pounds per cubic foot
Product Name: Filler foam Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Compression Strength At 25 Pct Deflection:
Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	0.35 pounds per square inch
Special Features: Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Product Name:
Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Filler foam
Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd" near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a Unit Of Measure:	Special Features:
near upper left corner (with far side up) and part number near lower left corner Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Rectangular with 2 cutouts on left/long edge: 1.25wx2.30h, 2.14 inches from bottom edge & 1.25wx3.00h, 8.92 from bottom; near side is
Material: Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	tapered 0.25 at bottom an has lengthwise grooves: 1.00wx1.12d, 4.15 & 7.90 inches from left edge; far side has markings: "up" & "fwd"
Plastic, polyurethane Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	near upper left corner (with far side up) and part number near lower left corner
Material: Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Material:
Plastic polyurethane Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Plastic, polyurethane
Supplementary Features: Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Material:
Material to be reticulated foam per sm-alc specification ms-mmrs-87-100 Shelf Life: N/a	Plastic polyurethane
Shelf Life: N/a	Supplementary Features:
N/a	Material to be reticulated foam per sm-alc specification ms-mmrs-87-100
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	-
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
T258-d	T258-d