

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2019>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.640 inches

Thickness:

4.000 inches

Length:

20.890 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left edge: 1.00wx1.00h, 2.50 & 14.00 inches from bottom; near side is tapered 0.50 at bottom and has crosswise groove, 1.20wx1.70d along right edge and markings: "up" & "aft" on 2 lines near center top and part number near center bottom; far side has lengthwise cutout along left edge: 5.76wx2.00d, a crosswise groove, 2.44wx1.60d from cutout on left to right edge, and a rectangular cutout at bottom right corner: 7.42wx2.84.1.75d

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d