

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2019>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.640 inches

**Thickness:**

4.000 inches

**Length:**

20.890 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 2 cutouts on left edge: 1.00wx1.00h, 2.50 & 14.00 inches from bottom; near side is tapered 0.50 at bottom and has crosswise groove, 1.20wx1.70d along right edge and markings: "up" & "aft" on 2 lines near center top and part number near center bottom; far side has lengthwise cutout along left edge: 5.76wx2.00d, a crosswise groove, 2.44wx1.60d from cutout on left to right edge, and a rectangular cutout at bottom right corner: 7.42wx2.84.1.75d

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T258-d