

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2687>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.200 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on left edge: 1.25wx1.00h, 3.28 & 14.10 inches from bottom edge and a cutout on the bottom edge: 8.60wx0.40h, 7.40 from left edge; near side has 2 lengthwise grooves: 1.12wx1.76d, 9.50 from left edge and 3.90 from right edge; there is a center cutout: 5.88wx7.00h, between the grooves, 5.00 inches from bottom edge with a line cut through from bottom of cutout to bottom of item, 13.09 inches from left edge; far side is tapered 0.56 at bottom edge and has markings: "up" & "aft" on 2 lines in center top area and part number centered in upper left area

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d