

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2726>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.900 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: 1.25wx1.18h, 1.88 inches from bottom & 1.25wx1.32h, 15.64 from bottom; an oval cutout centered lengthwise 13.09 inches from left edge, arcs at each end have radius 2.00 in with lower arc centered 7.70 inches from bottom & upper one, 11.06 from bottom with a line cut through from top of cutout to top of piece, 13.09 from left edge; near side has 2 lengthwise grooves: 2.50wx0.56d along top edge & 1.88wx0.56d along bottom edge; far side has markings: "up" & "aft" on 2 lines in upper left corner (far side up) & part number in upper right one

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d