

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2732>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.400 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Erectangular with 2 cutouts on left/short edge: 1.25wx1.52h, 2.00 inches from bottom edge & 1.25wx1.76h, 1.24 from top edge; an oval cutout with arcs at each end with radii of 2.00 inches, centered 13.09 from left edge and lower arc centered 8.20 from bottom & upper one, 11.50 up with line cut through from top of cutout to top of item, 13.09 from left edge; near side is tapered 0.26 at top edge and has 2 lengthwise grooves: 2.00wx0.56d along bottom edge & 2.52wx0.60d along top; far side is tapered 0.24 along bottom and has 2 lengthwise grooves: 2.36wx0.86d along bottom & 2.24wx0.72d along top and has markings: "up" & "aft" on 2 lines near upper left corner (far side up) & part number near upper right one

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d