

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2741>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.200 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle; 2 cutouts on left/short edge: 1.25wx1.54h, 2.00 from bottom & 1.25wx2.12h, 2.00 from top & cutout on top edge: 3.80wx2.00h, 2.03 from right; near side is tapered 0.32 at top edge and has lengthwise grooves: 2.00hx0.60d along bottom edge & 2.60wx0.70d along top & crosswise groove: 3.80wx3.00h, 2.04 from right edge; a nearly oval cutout with radius of 2.00 centered 13.09 from left with lower arc centered 8.48 from bottom, jutting to left for 1.00 inch 8.48 from bottom, then up to bottom of near side groove, right along groove for 3.00 in. Then down 1.76 to meet top of upper arc, centered 11.84 from bottom, ending with right side of oval; far side is tapered 0.20 at bottom edge and has markings: "up" & "aft" below groove in upper left area dn part number in upper right area (far side up)

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d