

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2871>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.750 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle; 3 cutouts on left/short edge: 1.25wx1.18h, 2.12 from bottom, 1.25wx1.00h, 5.96 from bottom & 1.25wx1.76h, 2.03 from top; a trapezoidal cutout with base on far side: 5.48wx4.50h, 9.96 from bottom & 15.00 from left edge & top/near side: 10.08wx4.05h, 8.76 from bottom & 3.52 from left edge with circular cutout at bottom right corner with radius of 4.00 inches, centered 13.09 from left and 8.64 from bottom; near side is tapered 0.28 at top edge; far side has lengthwise grooves: 2.12wx0.80d along bottom edge & 2.03wx0.64 along top & markings: "up" & "aft" to left of center cutout (far side up) and part number in upper right corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d