

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2876>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.360 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle; 3 cutouts on left/short edge: 1.25wx1.38h, 2.12 from bottom edge, 1.25wx1.00h, 6.16 from bottom, 1.25wx6.72h, 8.60 from bottom; near side is tapered 0.36 at top edge; far side has 2 lengthwise grooves: 2.12wx2.24d along bottom edge & 2.04wx2.04d along top edge & markings: "up" & "aft" in top left corner (far side up) & part number in bottom groove at left; there is acircular cutout near center: 4.00 in diam, centered 8.80 from bottom & 13.09 from left side with line cut through to bottom edge 13.09 from left 7 triangular cutout with bottom surface 10.48wx4.50h, 10.20 from bottom edge & 15.88 from left edge, slanting up to meet top surface 5.40 from left & 8.60 from bottom edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d