

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2877>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.560 inches

Thickness:

4.000 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle; 3 cutouts on left/short edge: 1.25wx1.30h, 2.00 from bottom, 1.25wx1.00h, 6.20 from bottom & 1.25wx1.56h, 12.96 from bottom; circle cutout with diam of 4.00 centered 13.09 from left edge & 8.88 from bottom with line cut through to bottom edge, 13.09 from left; triangular cutout along left edge with base on far side: 5.20wx4.50h, 8.80 from bottom, slanting up to meet left edge, 2.00 from top surface; far side has markings: "up" & "aft" on 2 lines near upper right corner (far side up) & part number near upper left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d