

View Online at <https://aerobasegroup.com/nsn/9330-01-502-2878>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.500 inches

Thickness:

2.500 inches

Length:

23.400 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle; 3 cutouts on left/short edge: 1.25wx1.00h, 1.64 & 5.00 from bottom edge & 1.25wx1.22h, 12.32 from bottom; a circle cutout with diameter of 4.00, centered 13.09 from left & 8.64 from bottom edge with line cut through to bottom edge, 13.09 from left edge; near side is tapered 0.58 at top edge and has 2 crosswise grooves: 1.00wx1.25d, 8.70 & 16.50 from left edge; far side has markings: "up" & "aft" at center top & part number to left

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T258-d