

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3028>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.090 inches

**Thickness:**

6.790 inches

**Length:**

24.370 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Irregularly shaped: see drawing for details; far side has 30 degree cutout along right/long edge (far side up) and roughly triangular cutout on left edge, 15 -30 degrees from top surface to bottom surface & is marked ""fwd" lengthwise along lower right edge & "up" & p/n lengthwise along upper left edge; near side has lengthwise cutout starting at bottom 30 degree cut, slanting up to point 2.00 from bottom & 15.84 from right, then to point 3.45 up & 11.65 from right, to 0.50 from top & 9.71 from rt, to top, 4.85 from rt, then to 0.50 from top at right edge; top surface has graduated lengthwise angles - see drawing; bottom edge has 30 degree crosswise cutout (o at far surface to 30 at top); there is a v-shaped cutout: 30 degrees toward bottom edge, 9.37 from bottom & 30 degrees toward top edge, 11.73 from bottom

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d