

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3028>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.090 inches

Thickness:

6.790 inches

Length:

24.370 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Irregularly shaped: see drawing for details; far side has 30 degree cutout along right/long edge (far side up) and roughly triangular cutout on left edge, 15 -30 degrees from top surface to bottom surface & is marked ""fwd" lengthwise along lower right edge & "up" & p/n lengthwise along upper left edge; near side has lengthwise cutout starting at bottom 30 degree cut, slanting up to point 2.00 from bottom & 15.84 from right, then to point 3.45 up & 11.65 from right, to 0.50 from top & 9.71 from rt, to top, 4.85 from rt, then to 0.50 from top at right edge; top surface has graduated lengthwise angles - see drawing; bottom edge has 30 degree crosswise cutout (o at far surface to 30 at top); there is a v-shaped cutout: 30 degrees toward bottom edge, 9.37 from bottom & 30 degrees toward top edge, 11.73 from bottom

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d