

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3042>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.760 inches

**Thickness:**

6.790 inches

**Length:**

24.620 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Irregularly shaped - see drawing for details; far side has 30 degree cutout along left/long edge (far side up) & roughly triangular cutout along right edge, 30 to 15 degrees top to bottom (far side up) and is marked along left edge: "fwd" near boot corner, "up" in center & part number near top; near side slants crosswise from bottom 30 degree cut to 0.50 from top, 9.71 from left edge, on to meet top, 4.85 from left & back to 0.50 from top at left edge; upper surface has graduated lengthwise angles; bottom edge has crosswise cut of 30 degrees, bottom surface to top surface; there is a v-shaped cutout, with 1 side starting 9.37 inches from bottom edge & 2.00 inches deep, at 30 degree angle toward top surface & toward bottom edge & opposite cut from 11.75 from bottom edge, 2.00 deep, 30 degrees toward top surface & toward top edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d