

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3042>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.760 inches

Thickness:

6.790 inches

Length:

24.620 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Irregularly shaped - see drawing for details; far side has 30 degree cutout along left/long edge (far side up) & roughly triangular cutout along right edge, 30 to 15 degrees top to bottom (far side up) and is marked along left edge: "fwd" near boot corner, "up" in center & part number near top; near side slants crosswise from bottom 30 degree cut to 0.50 from top, 9.71 from left edge, on to meet top, 4.85 from left & back to 0.50 from top at left edge; upper surface has graduated lengthwise angles; bottom edge has crosswise cut of 30 degrees, bottom surface to top surface; there is a v-shaped cutout, with 1 side starting 9.37 inches from bottom edge & 2.00 inches deep, at 30 degree angle toward top surface & toward bottom edge & opposite cut from 11.75 from bottom edge, 2.00 deep, 30 degrees toward top surface & toward top edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d