Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-3055

Fire Retarding Characteristic:

Not fire retarding

Width:

17.750 inches

Thickness:

6.720 inches

Length:

21.820 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Roughly rectangular; left/short edge tapers 1.00 at bottom edge; bottom edge has cutout: 15.20wx1.00h, 5.62 from left/tapered edge; top surface curves with radius of 40.25 from thickness of 6.72 along bottom edge to 2.50 along top edge; there are 2 parallel, slanted straight line cutouts along left edge: 1.75wx0.50h, 1.25 inches from top edge, slanting 15 degrees toward top surface & toward bottom edge & one 8.00 inches from top edge; far side is marked: "up" & "inbd" on 2 lines near center top, "fwd" to right (far side up) & part number in lower left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d