

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3070>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.730 inches

**Thickness:**

6.720 inches

**Length:**

21.620 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Roughly rectangular: left/short edge tapers 1.00 at bottom edge & has 2 cutouts: 2.00wx0.50h, 4.08 & 11.84 from bottom; bottom edge has cutout: 15.92wx0.58h, 5.72 from left; far side: surface is curved with radius of 40.28 from thickness of 6.72 along bottom edge to 2.50 thick along top; near side: has cuts 1.91 inches deep, 3.00 from bottom at left edge horizontally 9.25 inches then down to bottom edge and 1.91d, 11.25 from left, at bottom edge, up to 5.75 from bottom cutout, then over to right edge, & 1.91d, 2.00 above last line lengthwise to opposit edge; near side is marked "fwd" near top left corner, "up" & "inbd" near top right corner & part number near bottom right corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d