

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3351>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

11.890 inches

**Thickness:**

4.000 inches

**Length:**

38.620 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with long sides horizontal, has a key-shaped cutout in center: oval at left end has radius of 3.50 at each end, left arc centered 15.13 from left & 6.34 from top, right arc centered 23.57 from left, 6.34 from top, oval is cut through at angle so horizontal center on far side is 5.36 from top; cutout on right edge of oval: 3.56wx1.75h, 4.02 from top & cutout on bottom edge of this one: 3.00wx3.15h, 32.06 from left & 5.77 from top with line cut through from bottom of this cutout to bottom of item, 30.56 from left edge; near side is marked: "fwd" & "up" on 2 lines in upper right corner & with part number in lower left corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d