Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-3351

Fire Retarding Characteristic:

Not fire retarding

Width:

11.890 inches

Thickness:

4.000 inches

Length:

38.620 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with long sides horizontal, has a key-shaped cutout in center: oval at left end has radius of 3.50 at each end, left arc centered 15.13 from left & 6.34 from top, right arc centered 23.57 from left, 6.34 fromtop, oval is cut through at angle so horizontal center on far side is 5.36 from top; cutout on right edge of oval: 3.56wx1.75h, 4.02 from top & cutout on bottom edge of this one: 3.00wx3.15h, 32.06 from left & 5.77 from top with line cut through from bottom of this cutout to bottom of item, 30.56 from left edge; near side is marked: "fwd" & "up" on 2 lines in upper right corner & with part number in lower left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T258-d