

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3364>

Fire Retarding Characteristic:

Not fire retarding

Width:

11.890 inches

Thickness:

4.000 inches

Length:

38.620 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular, long sides horizontal, 2 cutouts: oval on right has radius of 1.50 with left arc centered 30.55 from left edge & 6.22 from top, right arc centered 32.93 from left & 6.22 from top with line cut through from rt edge of cutout to rt edge of item, 6.22 from top; kidney-shaped cutout to left: left arc has radius 1.50, centered 15.15 from left edge & 7.30 from top, rt arc has radius 2.00, 19.31 from left & 7.30 from top with line cut through from bottom of cutout to bottom of item, 15.15 from left; kidney cutout is cut at a slant from near side to far side so that horizontal center on far side is 6.34 from top; near side is marked "fwd" & " up" on 2 lines near top center & with part number in lower right corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d