

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3508>

Fire Retarding Characteristic:

Not fire retarding

Width:

15.850 inches

Thickness:

6.790 inches

Length:

24.370 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Irregularly shaped - see drawing for details; left long edge tapers to 15.85 wide at top edge & has cutout beginning on far surface, 1.75 from left edge, up at 30 degree angle to edge then up & right to 14.91 from right edge & 2.00 from farside, up & rt to 10.71 from rt & 3.45 from far side, to 8.71 from rt & 0.50 from top, to 4.48 from rt at top, to 0.50 from top at rt edge; top surface has graduated lengthwise angles; rt edge has roughly triangular cutout from near surface to far one, with 15 to 30 degree cuts, ending 4.48 from right edge at far surface; far side is marked: "up fwd" near left long edge, right corner & with part number near the center of that edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d