

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3508>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

15.850 inches

**Thickness:**

6.790 inches

**Length:**

24.370 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Irregularly shaped - see drawing for details; left long edge tapers to 15.85 wide at top edge & has cutout beginning on far surface, 1.75 from left edge, up at 30 degree angle to edge then up & right to 14.91 from right edge & 2.00 from farside, up & rt to 10.71 from rt & 3.45 from far side, to 8.71 from rt & 0.50 from top, to 4.48 from rt at top, to 0.50 from top at rt edge; top surface has graduated lengthwise angles; rt edge has roughly triangular cutout from near surface to far one, with 15 to 30 degree cuts, ending 4.48 from right edge at far surface; far side is marked: "up fwd" near left long edge, right corner & with part number near the center of that edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d