NSN 9330-01-502-3655

Cellular Plastic Material - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/9330-01-502-3655

Fire Retarding Characteristic:
Not fire retarding
Width:
16.210 inches
Thickness:
6.710 inches
Length:
33.710 inches
End Application:
Aircraft, thunderbolt ii, a-10
Surface Condition:
Rough
Density Rating:
1.2 pounds per cubic foot
Compression Strength At 25 Pct Deflection:
0.35 pounds per square inch
Product Name:
Filler foam
Special Features:
Trapezoidal in shape with near surface rounded with radius of 40.25 inches from top edge to bottom edge; 2 cutouts on right edge:
1.75wx0.75h, 2.37 & 8.90 inches from bottom edge; right edge has circular cutout, centered 6.20 inches from bottom, along far surface,
going left 5.26 inches then down at 45 degree angle to bottom edge; left edge has circular cutout centered 4.60 from bottom edge, going
right 7.50 inches then up at 45 degree angle to top edge; far side is marked: "fwd" in upper left corner (far side up) & "up" & "inbd" on 2 lines
in upper right corner & with part number in lower right corner
Material:
Plastic, polyurethane
Material:
Plastic polyurethane
Supplementary Features:
Material to be reticulated foam per sm-alc specification ms-mmrs-87-100
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T258-d