

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3655>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.210 inches

Thickness:

6.710 inches

Length:

33.710 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Trapezoidal in shape with near surface rounded with radius of 40.25 inches from top edge to bottom edge; 2 cutouts on right edge: 1.75wx0.75h, 2.37 & 8.90 inches from bottom edge; right edge has circular cutout, centered 6.20 inches from bottom, along far surface, going left 5.26 inches then down at 45 degree angle to bottom edge; left edge has circular cutout centered 4.60 from bottom edge, going right 7.50 inches then up at 45 degree angle to top edge; far side is marked: "fwd" in upper left corner (far side up) & "up" & "inbd" on 2 lines in upper right corner & with part number in lower right corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d