

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3706>

Fire Retarding Characteristic:

Not fire retarding

Width:

25.440 inches

Thickness:

4.000 inches

Length:

29.580 inches

End Application:

Missile, minuteman Igm-30

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Roughly rectangular with upper corners cut off at 30 degree angle, 19.40 from bottom; right edge has cutout 1.50wx7.0h, 1.67 inches from bottom; top edge has cutout starting 17.22 from right edge, extending to right edge; left top corner has arched cutout with radius of 2.5 centered 22.22 from right edge & 23.22 from bottom; center area has 3 cutouts: rectangle 1.50wx5.25hx1.50d, 16.97 from right edge & 17.14 from bottom, an arch with radius or 2.75 centered 22.22 from right & 14.39 from bottom then extending 9.50 to the right, a "finger" with radius or 3.0 from bottom edge of arch in 90 degree arc, then straight down with diameter of 3.25 ending with circle centered 10.16 from right edge & 4.39 from bottom; near side is marked "up" & "aft" on 2 lines near center top & with part number below & to the right

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d