

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3738>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

25.440 inches

**Thickness:**

4.000 inches

**Length:**

27.680 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Erectangle with both upper corners cut off at 30 degree angle, 17.32 inches from bottom edge & with oval cutouts on both cutoff edges with radius of 2.50 inches, centered 20.00 from bottom, on cut edges ending with curve with same radius centered 7.00 up the cutoff edges; 3 cutouts: circle with radius of 1.00, centered 1.92 from right & 4.08 from bottom, kidney shape with lower radius 1.00, centered 2.10 from right & 7.68 from bottom & upper radius 1.75, centered 2.72 from right & 10.18 from bottom, and somewhat oval shape, lower arc with 1.75 radius, centered 17.08 from right & 3.23 up, upper right arc, radius 1.75, 20.72 from right & 11.28 from bottom, upper left arc, 1.75 radius, 22.72 from right & 10.18 from bottom, & "bump" on left edge with radius of 0.50, 23.52 from right & 7.63 from bottom; near side is marked: "up" & "aft" on 2 lines near center top with part number centered below; far side has "up" & "fwd" on 2 lines in upper center right area

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d