

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3759>

Fire Retarding Characteristic:

Not fire retarding

Width:

25.440 inches

Thickness:

4.000 inches

Length:

27.140 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle with upper corners cut off at 30 degree angle 20.08 from bottom/short edge & with oval cutouts on both cutoff edges, with 2.50 radii & lower arcs centered 27.14 from bottom edge, then extending along cutoff edge 7.00 inches to upper arc; 2 more cutouts: rounded trapezoid along left edge, lower right corner rounded to radius of 1.75, centered 3.84 from left edge & 6.08 from bottom & upper rt corner with 1.75 radius centered 2.72 from left & 10.84 from bottom; kidney shape, with lower arc with 1.00 radius, 1.72 from right & 8.09 from bottom, upper arc with radius of 1.75, 2.72 from right & 10.84 from bottom; near side is marked: "up" & "aft" in upper center right area & with part number centered below it; far side has "up" & "fwd" in upper right center (far side up)

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d