

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3759>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

25.440 inches

**Thickness:**

4.000 inches

**Length:**

27.140 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangle with upper corners cut off at 30 degree angle 20.08 from bottom/short edge & with oval cutouts on both cutoff edges, with 2.50 radii & lower arcs centered 27.14 from bottom edge, then extending along cutoff edge 7.00 inches to upper arc; 2 more cutouts: rounded trapezoid along left edge, lower right corner rounded to radius of 1.75, centered 3.84 from left edge & 6.08 from bottom & upper rt corner with 1.75 radius centered 2.72 from left & 10.84 from bottom; kidney shape, with lower arc with 1.00 radius, 1.72 from righ & 8.09 from bottom, upper arc with radius of 1.75, 2.72 from right & 10.84 from bottom; near side is marked: "up" & "aft" in upper center right area & with part number centered below it; far side has "up" & "fwd" in upper right center (far side up)

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d