

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3768>

Fire Retarding Characteristic:

Not fire retarding

Width:

17.710 inches

Thickness:

4.000 inches

Length:

38.140 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangle with cutout from bottom/long & lower right edges: rectangular cutout , 30.44wx5.00h from right corner; semicircle with 9.00 radius, centered 18.44 from right on cut edge; a semicircle with 2.50 radius, centered 20.94 from right on same cut edge, overlapping first circle; bottom left edge is cut at angle toward cutouts (approximately 22 degree angle), there is a groove: 1.50wx1.75d along this bottom edge; near side is marked: "fwd" & "up" on 2 lines, crosswise, near center of left edge & with part number, lengthwise, near upper left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d