

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3941>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.500 inches

Thickness:

4.000 inches

Length:

25.440 inches

End Application:

Missile, minuteman lgm-30

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on bottom/long edge: 2.16wx2.25h at bottom right corner & 2.16wx1.75h at bottom left; 2 cutouts on top edge: beginning 9.32 from either side edge, down 2.50 inches then down & toward side, ending 3.50 from top edge; a kidney shaped cutout with lower arc with 3.00 radius centered 7.72 from left edge & 10.25 from top & upper arc with 3.50 radius centered 12.72 from left edge & 7.75 from top; far side has 3.00 inch deep groove 2.42 inches from right (cut) edge across to the right edge, extending down 5.00 from top edge then slanting toward right, ending at the right edge, 7.25 from top & an arched groove below this cutout, 0.725 inches in from right edge, 2.75wx3.00 deep; near side is marked: "fwd up" at center top & with part number near center of right edge

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d