

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3941>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

18.500 inches

**Thickness:**

4.000 inches

**Length:**

25.440 inches

**End Application:**

Missile, minuteman lgm-30

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with 2 cutouts on bottom/long edge: 2.16wx2.25h at bottom right corner & 2.16wx1.75h at bottom left; 2 cutouts on top edge: beginning 9.32 from either side edge, down 2.50 inches then down & toward side, ending 3.50 from top edge; a kidney shaped cutout with lower arc with 3.00 radius centered 7.72 from left edge & 10.25 from top & upper arc with 3.50 radius centered 12.72 from left edge & 7.75 from top; far side has 3.00 inch deep groove 2.42 inches from right (cut) edge across to the right edge, extending down 5.00 from top edge then slanting toward right, ending at the right edge, 7.25 from top & an arched groove below this cutout, 0.725 inches in from right edge, 2.75wx3.00 deep; near side is marked: "fwd up" at center top & with part number near center of right edge

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d