

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3943>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

13.340 inches

**Thickness:**

4.000 inches

**Length:**

22.750 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Irregularly shaped: see drawing for details; near side has 45 degree cut from far surface of top edge to 2.66 from top edge on near surface & markings: "fwd" & "up" on 2 lines in upper left cutout & part number in upper right one; top edge has 2 rectangular cutouts: 2.00wx3.34h, 4.02 & 17.02 from right edge; bottom edge has arched cutout with radius of 2.00 centered 6.46 from right edge & 1.92 from bottom, a lengthwise cutout 7.83ws1.92h, 14.92 from right edge; bottom left & bottom right corners are cut off irregularly; also a roughly t-shaped groove 2.75 deep with leg 14.92 from right on bottom edge of bottom cutout & crossbar slanting 45 degrees from left corner across leg to point 6.46 from right & 5.50 up, then down at 45 degrees to right corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d