

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3960>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

16.250 inches

**Thickness:**

4.000 inches

**Length:**

23.260 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

Rectangular with angled cutoff along top/long edge; from near surface at top edge to 5.50 from top on far surface; with cutouts on each top corner: with inner bottom corner a 90 degree arc with radius 1.25 centered 1.54 from outer edge & 4.81 from top with cutout extending horizontally & vertically to outer edges; an arched cutout, opening on top edge 12.31 & 17.31 inches from left edge, slanting down & to right with width of 5.00, ending in circle with 2.50 radius, centered 16.95 from left & 3.62 from bottom; a line cut thru, 1.56 from left cut edge at top edge, vertically down 5.5 inches on near surface & slanting down to 6.75 inches from bottom on far surface; near side is marked "fwd" & "up" on 2 lines at left top & with part number in lower left corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d