

View Online at <https://aerobasegroup.com/nsn/9330-01-502-3960>

Fire Retarding Characteristic:

Not fire retarding

Width:

16.250 inches

Thickness:

4.000 inches

Length:

23.260 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with angled cutoff along top/long edge; from near surface at top edge to 5.50 from top on far surface; with cutouts on each top corner: with inner bottom corner a 90 degree arc with radius 1.25 centered 1.54 from outer edge & 4.81 from top with cutout extending horizontally & vertically to outer edges; an arched cutout, opening on top edge 12.31 & 17.31 inches from left edge, slanting down & to right with width of 5.00, ending in circle with 2.50 radius, centered 16.95 from left & 3.62 from bottom; a line cut thru, 1.56 from left cut edge at top edge, vertically down 5.5 inches on near surface & slanting down to 6.75 inches from bottom on far surface; near side is marked "fwd" & "up" on 2 lines at left top & with part number in lower left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d