

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4009>

Fire Retarding Characteristic:

Not fire retarding

Width:

26.110 inches

Thickness:

4.000 inches

Length:

38.140 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

5rectangular with 2 circular cutouts with radii of 7.00 inches, one centered 38.14 inches from right/short edge & 13.06 from bottom; other, 16.88 from right & 15.31 from bottom; a cutout from bottom right corner, 4.50wx5.00h, which then winds up & to the left, ending in circle with 1.75 radius, centered 22.12 from right - see drawing for details; also 2 grooves 2.00 inches deep: one 1.12 from outer edge, extending upward from cutout, ending in circle with 1.75 radius centered 17.51 from bottom & 2.87 from right edge, the other extending at 45 degree angle from perpendicular turn in cutout downward toward bottom edge; near side is marked "fwd" & "up" on 2 lines, crosswise, near center of left edge & with part number, lengthwise, in upper left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d