

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4009>

**Fire Retarding Characteristic:**

Not fire retarding

**Width:**

26.110 inches

**Thickness:**

4.000 inches

**Length:**

38.140 inches

**End Application:**

Aircraft, thunderbolt ii, a-10

**Surface Condition:**

Rough

**Density Rating:**

1.2 pounds per cubic foot

**Compression Strength At 25 Pct Deflection:**

0.35 pounds per square inch

**Product Name:**

Filler foam

**Special Features:**

5rectangular with 2 circular cutouts with radii of 7.00 inches, one centered 38.14 inches from right/short edge & 13.06 from bottom; other, 16.88 from right & 15.31 from bottom; a cutout from bottom right corner, 4.50wx5.00h, which then winds up & to the left, ending in circle with 1.75 radius, centered 22.12 from right - see drawing for details; also 2 grooves 2.00 inches deep: one 1.12 from outer edge, extending upward from cutout, ending in circle with 1.75 radius centered 17.51 from bottom & 2.87 from right edge, the other extending at 45 degree angle from perpendicular turn in cutout downward toward bottom edge; near side is marked "fwd" & "up" on 2 lines, crosswise, near center of left edge & with part number, lengthwise, in upper left corner

**Material:**

Plastic, polyurethane

**Material:**

Plastic polyurethane

**Supplementary Features:**

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T258-d