

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4023>

Fire Retarding Characteristic:

Not fire retarding

Width:

26.110 inches

Thickness:

4.000 inches

Length:

38.140 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with 2 cutouts on right/short edge: one with 1.50 radius, centered 2.08 from right & 2.50 from top extending from horizontal diameter to right edge & up to top edge, other with 1.50 radius, centered 2.08 from right & 17.31 from top extending from hor. Diam to right edge & to bottom edge; circular cutout, 3.50 radius, centered 27.60 from right & 13.06 from bottom; circular cutout, 1.50 radius, centered 17.70 from right & 15.31 from bottom; a cutout 5.00wx4.00h, 8.08 from right & 11.38 from bottom; a circular groove on far side surface with 1.50 radius, centered 0.50 from far surface at 45 degree angle across bottom right corner, centered on right edge 4.81 inches from bottom edge; near side is marked: "fwd" & "up", crosswise, near upper left corner & with part number, lengthwise, in upper left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d