

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4056>

Fire Retarding Characteristic:

Not fire retarding

Width:

11.640 inches

Thickness:

6.750 inches

Length:

38.140 inches

End Application:

Aircraft, thunderbolt ii, a-10

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular; far side has lenthwise groove along top edge, 1.00d, tapering from 4.00w at right edge (near side up) to 3.00 deep at left edge; an arched cutout along top surface, 3.00w, 1.12 inch from right edge, ending in circle centered 2.67 from right & 4.87 from top; a semicircular groove on far surface with 1.48 radius, centered 23.81 from right edge at top edge, angling down and to right then over to right edge, ending 5.00 from top -see drawing for details; near side is marked: "fwd" & "up" on 2 lines in upper left corner & with part number in lower left corner

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d