

View Online at <https://aerobasegroup.com/nsn/9330-01-502-4070>

Fire Retarding Characteristic:

Not fire retarding

Width:

18.500 inches

Thickness:

4.000 inches

Length:

21.340 inches

End Application:

Missile, minuteman lgm-30

Surface Condition:

Rough

Density Rating:

1.2 pounds per cubic foot

Compression Strength At 25 Pct Deflection:

0.35 pounds per square inch

Product Name:

Filler foam

Special Features:

Rectangular with cutout at lower right corner, 4.60wx2.46h; a kidney shaped cutout with one end having a 2.00 radius, centered 3.42 from left edge & 10.25 from top & other end with 3.50 radius, centered 8.42 from left & 8.00 from top; a semicircular groove on far side surface with 1.50 radius, 2.25 deep, centered 3.22 from left at top edge (near side up) & extending 11 degrees down to left edge; a trapezoidal groove on far side surface, 2.65 deep with endpoints 12.12 & 19.92 inches from left at top edge and 15.37 & 19.92 from left at bottom edge; near side is marked "fwd up" at center top & with part number below kidney cutout

Material:

Plastic, polyurethane

Material:

Plastic polyurethane

Supplementary Features:

Material to be reticulated foam per sm-alc specification ms-mmrs-87-100

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T258-d